

Eagle Chemical B42 BLUE

Liquid Runway Deicer

AMS 1435E Certified



Why Eagle Chemical B42 BLUE?

Eagle Chemical B42 BLUE liquid runway deicer is a high-performing 50% aqueous potassium acetate solution by weight. B42 BLUE contains a Blue colorant, enabling rapid identification of application areas and splash zones near or on sensitive equipment, this feature allows for quick detection and removal from unintended surfaces. It contains no urea or glycol and is stable in storage with no agitation required. B42 BLUE also exhibits exceptional corrosion resistance. It is the industrial standard for use on airport runways. B42 BLUE can be used as an anti-icer or deicer.

BENEFITS

- Colored blue for enhance visibility
- Less slippery than hybrid/glycol-based products
- Remains stable and effective long term when stored as directed
- Non-corrosive

PERFORMANCE

- Industrial leading anti-icing characteristics
- Low viscosity, sprays effectively at low temperatures
- Effective at -26°F (-32°C)
- Low Freezing Point -76°F (-60°C)

ENVIRONMENT

- Readily biodegradable low BOD and COD
- Low toxicity to fish and mammals; recognized as “relatively harmless” by the U.S. Fish and Wildlife Scale
- Does not contain urea or glycol

APPLICATION

- Anti-icing: 0.5 gallons/1000ft² (25g/m²)
- Deicing: 1 gallon/1000ft² (50 g/m²) near 32°F on thin ice; 3 gallon/1000ft² (150 g/m²) near 10°F on thick ice
- Re-apply when new accumulation shows first tendency to bond
- Plow and broom often to reduce fluid dilution

Eagle Chemical B42 BLUE

Liquid Runway Deicer

AMS 1435E Certified



Product Specifications

Composition	Appearance	Density	Viscosity
50% Potassium acetate solution, by weight	Blue (transparent), free from matter in suspension	10.8 lbs/gallon	At 32°F (0°C) = 12cP
Flash Point	Freezing Point	Miscibility	pH
Nonflammable	-76°F (-60°C)	Complete	9.0-10.0
Specific Gravity	BOD5 @68°F (20°C)	COD	LC ₅₀ (fish; 96hr)
1.27-1.30	0.19 kg O ₂ /kg fluid	0.34 kg O ₂ /kg fluid	2,450 mg/L
Packaging		Handling	
55 gallon drums (208 liters) – 4 drum minimum 275 gallon totes (1041 liters) – 1 tote minimum Bulk - 4400 gallon (16,656 liters) minimum		- B42 should not be plumbed through systems that use galvanized, zinc, or brass components - HDPE or stainless steel containers are preferred, otherwise use carbon or low alloy steel if clean and free of rust, surface deposits, and residues - Best practice include storing totes and drums in areas protected from weather and exposure to direct sunlight	